

FANYUAN INSTRUMENT (HF) CO., LTD. DOWELL SCIENCE AND TECHNOLOGY (HK) CO., LTD.

ADD: Tianyuan Road 9#, High-tech Zone, Hefei City, China Postal Code: 230088

TEL: +86-551-65232508 FAX: +86-551-65232507 Email: sales@hkdowell.com Website: http://www.fyichina.com.cn

DW5076 AUTOMATIC FEATHER AND DOWN FILLING POWER TESTER





WWW. FYICHINA. COM. CN

FANYUAN INSTRUMENT (HF) CO., LTD. DOWELL SCIENCE AND TECHNOLOGY (HK) CO., LTD.

ADD: Tianyuan Road 9#, High-tech Zone, Hefei City, China Postal Code: 230088

TEL: +86-551-65232508 FAX: +86-551-65232507 Email: sales@hkdowell.com

Website: http://www.fyichina.com.cn

MODEL NO.

DW5076

Application:

DW5076 AUTOMATIC FEATHER AND DOWN FILLING POWER TESTER, is used to test the filling power (massic volume), is applicable to finished down and/or feathers, fit for or constituting filled manufactured articles (e.g. anoraks, quilts, etc.)

A test specimen, suitably prepared, having a specified mass is placed in a cylinder and the material is aerated by blowing for a set period. Pressure by way of a platen is then applied to the filling material at a constant speed and after a stipulated time the level of the platen is noted. The massic volume is calculated with regard to the height and the known diameter of the graduate cylinder.

Related Standards:

STANDARDS	IDFB-FP	BS EN12130	JIS L1903

Note: this tester can conform to but not limit to the standards above, for more standards conformance, please contact us.

Features:

- Large touch screen, man-machine conversation, brief and clear;
- Built-in printer, test result can be put out anytime;
- Automatic blow system keep the feather and down in a state of natural and fluey, make sure the good factuality and repeatability during every test;
- Special designed incline touch screen to facilitate watching the screen;
- Special designed filtration system make sure the specimen won't blowing everywhere;
- Measuring speed is adjustable for fit different standards;
- Unique zero system make sure the accuracy of test result;
- Visible cylinder;
- Standard pressing plate, make sure the feather and down under the standard pressure.

Key Specification:

Height of cylinder: 600mmMeasurement accuracy 0.1mm

• Inner diameter of cylinder 288mm

Confidential Page 2 of 3 8/17/2015



FANYUAN INSTRUMENT (HF) CO., LTD. DOWELL SCIENCE AND TECHNOLOGY (HK) CO., LTD.

ADD: Tianyuan Road 9#, High-tech Zone, Hefei City, China Postal Code: 230088

TEL: +86-551-65232508 FAX: +86-551-65232507 Email: sales@hkdowell.com

Website: http://www.fyichina.com.cn

Weight of pressing plateDiameter of pressing plate284mm

● Blow speed 3~5L/s

• Power supply AC220V \pm 10% 50Hz 100W

● Dimension 600 mm×500 mm×1300 mm

• Weight 30kg

Standard configuration:

No.	Item	Quantity
1	Main machine	1 set
2	Pressing plate	1 pcs

Optional Accessories:

No.	Item
1	HZY-A200 balance (200g, 0.01g)
2	Printer paper