



WWW.FYICHINA.COM.CN

FANYUAN INSTRUMENT (HF) CO., LTD.
DOWELL SCIENCE AND TECHNOLOGY (HK) CO., LTD.

ADD: Tianyuan Road 9#, High-tech Zone, Hefei City, China Postal Code: 230088

TEL: +86-551-65232508

FAX: +86-551-65232507

Email: sales@hkdownell.com

Website: <http://www.fyichina.com.cn>

Y089A/E FULLY AUTOMATIC WASHING SHRINKAGE TESTER



Stainless steel drum



MODEL NO.

Y089A/E

Application:

Fully Automatic Washing Shrinkage Tester. Accelerated washing apparatus for knitted and woven fabrics to assess shrinkage in accordance with international test methods. Also used for assessing fabric stability, color fastness, finish durability, spirality and pilling to washing.

Related Standards:

STANDARDS	ISO5077, 6330
-----------	---------------

Features:

- MCU program controller, build-in ten sets of washing program that ISO required, and operator program capability;
- No need to fix to ground with foot screw, operating stably;
- Soft link between rotating cage and rack, low vibration and noise;
- Variable frequency motor, switch smoothly between high speed and low speed, low temperature increment of motor,
- Blue fluorescence LCD display, test state dynamic icon shows, easier to catch the eye and operation convenience;
- Non-touch capacitance water level meter to measure water level accuracy and reliable;
- 5 more special washing modes for Brand Nike and Adidas.
- Fully stainless steel inside and outside (YG089E) .
- Fully stainless steel inside (YG089A).

Key Specification:

● Washing model:	front-loading, horizontal tumbling-box type		
● Diameter of tumbling-box:	515±5mm		
● Depth of tumbling-box:	335±5mm		
● Interval between inner and outer tumbling-box:	28±1mm		
● Number of lifter:	3		
● Height of lifter:	50±5mm		
● Rotating method			
Normal model:	clockwise rotating	12±0.1s,	pause 3±0.1s,
	anticlockwise rotating	12±0.1s,	pause 3±0.1s
Soft model:	clockwise rotating	3±0.1s,	pause 12±0.1s,

