

DW9430 BALLY WATERPROOFNESS PENETRATION TESTER



MODEL NO.

DW9430 (former model FY011)

APPLICATION:

DW9430 BALLY WATER-PROOF PENETRATION TESTER is used to test the waterproof performance of leather, artificial leather and fabrics. It acquires waterproof index by bending and folding the materials and the data can be used for improvement.



FANYUAN INSTRUMENT (HF) CO., LTD.
DOWELL SCIENCE AND TECHNOLOGY (HK) CO., LTD.
 ADD: Tianyuan Road 9#, High-tech Zone, Hefei City, China Postal Code: 230088
 TEL: +86-551-65232508
 FAX: +86-551-65232507
 Email: sales@hkdownell.com
 Website: <http://www.fyichina.com.cn>

RELATED STANARD

STANDARDS	ISO 17702	EN ISO 20344	SATRA TM171
------------------	-----------	--------------	-------------

Note: this tester can conform to but not limit to all the standards above, for more standards conformance, please contact us.

FEATURE:

- Internationally accepted testing method
- Adjustable amplitude
- Electronic counter per station
- Specified in many international and European standards
- Mechanically reliable

KEY SPECIFICATION:

- Test Position 4
- Test amplitude 2, 3, 4, 6mm
- Specimen size 75×60mm
- Test speed 50r/min
- Counter LCD display 0~999,999
- Power supply AC220V 50Hz
- Dimensions 420×600×510mm(W×D×H)
- Weight 55kg

STANDARD CONFIGURATION:

No.	Item	Quantity
1	Main machine	1 set

OPTIONAL ACCESSORIES:

No.	Item	Quantity
1	Digital balance (200g/0.01)	1set